

# 鎢鋼 滾磨刀



Product details




## Solid Carbides


高硬度鎢鋼製成，使用於雕刻、粗磨、成型。  
適合鐵及非鐵金屬、玻璃纖維、壓克力、塑膠等  
材質，亦適用於鎢鋼、陶瓷及硬化鋼材之切削。

Made of high hardness carbide. Ideal for  
engraving, roughing, and forming on ferrous  
metal, non-ferrous metal, glass fiber, acrylic,  
plastic, and wood etc.


### SA 圓筒形 Cylinder Shape



### SB 圓筒形 / EC Cylinder Shape / EC



### SC 圓筒 R 形 Cylinder Shape / Radius End



型號 MODEL	刃部直徑 Cutting Dia (D)	柄徑 Shank Dia (d)	刃部長度 Length of Cut (l)	總長 Overall Length (L)
SA-41M	1.5	3	6	38
SA-42M	2.5	3	11	38
SA-43M	3	3	14	38
SA-51M	6	3	12	51
SA-51M/EC	6	3	12	50
SA-52M	4	3	13	39
SA-53M	5	3	12.7	38
SA-13M	4	6	16	50
SA-14M	5	6	16	50
SA-1M	6	6	16	50
SA-2M	8	6	19	63
SA-3M	9.5	6	19	63
SA-5M	12.7	6	25	69
SA-6M	16	6	25	69
SA-7M	19	6	25	69
SA-9M	25	6	25	69


SB-43M	3	3	14	38
SB-51M	6	3	4.7	43
SB-13M	4	6	13	50
SB-14M	5	6	16	50
SB-1M	6	6	16	50
SB-2M	8	6	19	63
SB-3M	9.5	6	19	63
SB-5M	12.7	6	25	69
SB-6M	16	6	25	69

SC-41M	2.5	3	11	38
SC-42M	3	3	14	38
SC-51M	6.3	3	12.7	50
SC-52M	4	3	12.7	39
SC-53M	5	3	13	39
SC-13M	4	6	16	50
SC-14M	5	6	16	50
SC-1M	6	6	16	50
SC-2M	8	6	19	63
SC-3M	9.5	6	19	63
SC-5M	12.7	6	25	69
SC-6M	16	6	25	69
SC-7M	19	6	25	69
SC-9M	25	6	25	69


d: 交叉紋 (標準品) s: 單斜紋 (訂製品) nf: 鋁質及銅質用 (僅提供 6mm 柄)

d: double cut (standard) s: single cut (custom made) nf: nonferrous (only available for 6mm shank)


SD 球形  
Ball Shape




SE 蛋形  
Oval Shape



SF 桃形  
Tree Shape



SG 桃尖形  
Tree Shape Pointed End



型號 MODEL	刃部直徑 Cutting Dia (D)	柄徑 Shank Dia (d)	刃部長度 Length of Cut (l)	總長 Overall Length (L)
-------------	-------------------------	---------------------	---------------------------	--------------------------


SD-41M	2.5	3	2.5	38
SD-42M	3	3	2.8	38
SD-51M	6.3	3	5	44
SD-52M	4	3	3.8	39
SD-53M	5	3	4.7	39
SD-14M	5	6	4	50
SD-1M	6	6	5	50
SD-2M	8	6	6.4	50
SD-3M	9.5	6	8	52
SD-5M	12.7	6	11	55
SD-6M	16	6	14	58
SD-7M	19	6	16	62
SD-9M	25	6	21	72

SE-41M	3	3	5.5	38
SE-51M	6.3	3	9.5	51
SE-53M	5	3	7.1	39
SE-1M	6	6	9.5	50
SE-3M	9.5	6	16	60
SE-5M	12.7	6	22	66
SE-6M	16	6	25	69
SE-7M	19	6	25	69


SF-41M	3	3	6	38
SF-42M	3	3	12	38
SF-51M	6.3	3	12.7	51
SF-53M	5	3	13	38
SF-14M	19	6	32	76
SF-15M	19	6	38	82
SF-1M	6	6	16	50
SF-3M	9.5	6	19	63
SF-5M	12.7	6	25	69
SF-6M	16	6	25	69
SF-7M	19	6	25	69

SG-41M	3	3	6	38
SG-43M	3	3	10	38
SG-44M	3	3	12	38
SG-51M	6.3	3	12	51
SG-53M	5	3	13	39
SG-1M	6	6	16	50
SG-2M	8	6	16	63
SG-3M	9.5	6	19	63
SG-5M	12.7	6	25	69
SG-6M	16	6	25	69
SG-7M	19	6	25	69
SG-15M	19	6	38	82


SH 火焰形  
Flame Shape




SL 錐 R 形  
Taper Shape / Radius End



SM 圓錐形  
Cone Shape



SN 皇冠形  
Inverted Cone Shape



型號 MODEL	刃部直徑 Cutting Dia (D)	柄徑 Shank Dia (d)	刃部長度 Length of Cut (l)	總長 Overall Length (L)	角度 Angle (a)
-------------	-------------------------	---------------------	---------------------------	--------------------------	-----------------

SH-41M	3	3	6.3	38	-
SH-53M	5	3	9.5	39	-
SH-2M	8	6	19	63	-
SH-5M	12.7	6	32	76	-
SH-6M	16	6	36	80	-
SH-7M	19	6	41	85	-

SL-41M	3	3	6.5	38	8°
SL-42M	3	3	12.7	38	8°
SL-53M	5	3	12.7	38	14°
SL-1M	6	6	16	50	14°
SL-2M	8	6	22	69	14°
SL-3M	9.5	6	27	74	14°
SL-4M	12.7	6	28	76	14°
SL-5M	16	6	30	77	14°
SL-7M	19	6	38	85	14°

SM-41M	3	3	8.9	38	12°
SM-42M	3	3	11	38	14°
SM-43M	3	3	16	38	7°
SM-51M	6	3	12.7	51	22°
SM-53M	5	3	13	39	16°
SM-1M	6	6	12.7	50	22°
SM-2M	6	6	19	50	14°
SM-3M	6	6	25	50	10°
SM-4M	9.5	6	16	63	28°
SM-5M	12.7	6	22	69	28°
SM-6M	16	6	25	73	31°

SN-41M	2.5	3	3	38	10°
SN-42M	3	3	4	38	10°
SN-51M	6.3	3	6	51	10°
SN-53M	5	3	6.3	38	10°
SN-1M	6	6	8	50	10°
SN-2M	9.5	6	9	53	13°
SN-4M	12.7	6	12	57	28°
SN-6M	16	6	19	63	18°
SN-7M	19	6	16	60	30°

d: 交叉紋 (標準品) s: 單斜紋 (訂製品) nf: 鋁質及銅質用 (僅提供 6mm 柄)

d: double cut (standard) s: single cut (custom made) nf: nonferrous (only available for 6mm shank)